



ThermoPlus pool heat pump — appearance of the range

SPECIFICATION

Nominal heating capacity	15.5 kW	Circuit breaker note	Final circuit breaker to be specified by the electrician to AS/NZS 3000
Heating capacity, 27 °C air and 27 °C water	3.81–17.05 kW	Water flow rate	7.3 m³/h
COP, 27 °C air and 27 °C water	5.8–12.3	Water connections	40 mm
Heating capacity, 15 °C air and 26 °C water	3.0–12.43 kW	Heat exchanger	Spiral titanium coil in injection PVC shell
COP, 15 °C air and 26 °C water	4.4–6.6	Operating air temperature	–15 to 43 °C
Nominal rated input power	3.1 kW	Temperature setting	1 °C steps
Nominal rated input current	17.5 A	Refrigerant	R32
Maximum heating current	13.6 A	Sound level at 1 m	44–54 dB(A)
Power supply	220–240 V, single phase, 50 Hz	Dimensions, L × W × H	1110 × 416 × 711 mm
Suggested circuit breaker	25 A	Weight	61 kg
		Warranty	2 years parts and labour
		Manufacturer	Hot Water Heatpumps Ltd

CHAMPION HEATING LTD

Auckland hydronic and pool heating specialists.

Figures are manufacturer data and subject to change without notice. Champion Heating Ltd is an independent supplier and installer; brand names identify the products we supply.

0800 HEAT 4 U

0800 432 848 · M 021 527 974

info@championheating.co.nz · championheating.co.nz